Reka Glue Gun Pneumatic

reka**=**

Glue Gun TR 55 LCD



Fig. TR 55 LCD Glue Gun Made in Germany

The glue gun TR 55 LCD works with melting glues of high and low viscosities in granulate and stick forms.

You adjust the desired temperature between approx. 50 and 200°C; so you always operate at the temperature prescribed for the glue.

The electronic temperature control is integrated in the handle for easy operation.

It provides for the optimum operating temperature simultaneously ensuring a careful handling of the material to be glued. The electronic system responds to the slightest deviation.

Due to the extraordinarily low weight and the balanced design of the appliance the work is not

tiring and your wristle will not be strained.

The TR 55 LCD will become light as feathers when you fix them to a balancer.

Thanks to the great variety of Reka accessories you can choose an appliance configuration adapted to your individual requirements.

A stationary stand on which you may deposit the gun and the foot switch are helpful when you glue small parts. Both hands are free for an even more productive procedure.

Various nozzles, foot switches, balancers, stands on which the gun may be deposited and stands for stationary operation complete the program.

Subject to technical modifications



Technical Data

TR 55 LCD

Voltage 230 V (120 V on request)

Heating capacity 400 W

Air pressure for glue max. approx. 90 psi/6 bars *

Air consumption max. 100 I / min.

Temperature control electronic

Temperature control range 50-200°C

Overheat protection thermal protector

Fuse 4 A

Heat-up time 3 – 10 min. **
Length of electric cord approx. 8,5 m

Tank capacity330 mlMax. application of glue per minute330 mlWeight handgun1400 g

Accessories

Foot switch pneumatic
Stand <u>with</u> pressure regulator and manometer
Stationary equipment
Balancer

Various additional nozzles

★ Special nozzles available on request.

Reka Klebetechnik GmbH & Co.KG

Siemensstr. 6 D-76344 Eggenstein Tel. +49 721 / 970 780 Fax +49 721 / 705 069

Internet: www.reka-klebetechnik.de Email: info@reka-klebetechnik.de

Only in connection with pressure gauge; filter necessary.

^{**} Depending on type of adhesive.